

### REMOTE GENERATOR



Top cut: 376x376 mm  
Overall height: 186 mm  
Generator dim.: 308 X 330 X 65 mm.

### USER COMMANDS



Control knob +  
LED indicator



Control panel with LED display

**Ceramic glass dimensions:**  
diameter 300 mm, depth 70 mm,  
thickness 6 mm

**Commands:**

- Control knob with LED indicator
- Or Control panel with LED display

**Power ranges:** from 80 W to 4000 W or  
from 100 W to 6000 W

**Inductor diameter:** 290 mm

**Boil time of 2 liters of water with lid:**  
4 000W: 3 minutes, 6 000 W: 1mn50s.

Remote generator, ventilated inductor  
housing, distance between generator and  
inductor up to 5 m. Standard length of cable:  
2 meters. Price of the additional meter of  
cable: 20 €, ref : CABLI1

**Washable filter** built in the remote generator

**Type of use:** heavy duty

## PREMIUM benefits

- Temperature or power display
- Maintenance selection mode on the control panel
- USB connection kit with storage of hours of use and reading of error codes
- Interchangeable electronic cards available for immediate servicing
- Technical phone assistance and training

POWER	4 000 W	6 000 W
Power supply	400 V 40-60 Hz 3 phases 6 A + E	400 V 40-60 Hz 3 phases 9 A + E
Provided cable	4G2,5 mm <sup>2</sup> without plug	4G2,5 mm <sup>2</sup> without plug
REF Control panel + display	PWE4001BA	PWE6001BA
REF Control knob	PWE4001M	PWE6001M

Technical features available on [www.seipam.com](http://www.seipam.com)

