

# WOK INDUCTION

## 8 000 W - 10 000 W - 12 000 W

THREE PHASE

### USER COMMANDS



Control knob +  
LED indicator

### REMOTE GENERATOR



Top cut: 376 x 376 mm  
Overall height: 186 mm  
Generator dim: 360X460X160mm

#### Ceramic glass dimensions:

Diameter 300 mm, depth 70 mm,  
thickness 6 mm

#### Commands:

- Control knob with LED indicator

Inductor diameter: 275 mm

#### Boil time of 2 liters of water with lid:

8 000 W: 1mn20s, 10 000 W:  
1mn5s, 12 000 W: 57s

#### INFRAPAM™ patent:

Overheating detection and infrared  
control system

Remote generator, Ventilated inductor  
housing, distance between generator and  
inductor up to 5 m. Standard length of cable:  
2 meters. Price of the additional meter of  
cable: 20€, ref: CABLI1

**Washable filter** built in the remote generator

**Type of use:** heavy duty

POWER	8 000 W	10 000 W	12 000 W
Power supply	400 V 40-60 Hz 3 phases 12 A + E	400 V 40-60 Hz 3 phases 15 A + E	400 V 40-60 Hz 3 phases 22 A + E
Provided cable	4G2,5mm <sup>2</sup> without plug	4G2,5mm <sup>2</sup> without plug	5G4mm <sup>2</sup> without plug
REF Control knob	EWD8001M	EWD10001M	EWD12001M