

WOK INDUCTION 3 500 W - 5 000 W

SINGLE PHASE

BUILT IN

INTEGRATED GENERATOR



Top cut: 376 x 376 mm
Overall height: 186 mm

REMOTE GENERATOR



Top cut: 376 x 376 mm
Overall height: 186 mm
Generator dim: 300 x 300 x 100 mm

USER COMMANDS



Control knob +
LED indicator



1 hob control panel

Ceramic glass dimensions:
diameter 300 mm, depth 70 mm,
thickness 6 mm

Commands

- Touch control panel with 20 levels of power from 140W to 3500W or from 200W to 5000W
- or control knob with LED indicator

Recommended Utensils: wok pans \varnothing 360
(available in stock)

Inductor diameter 3 500 W: 210 mm,
5 000 W: 230 mm

Boil time of 2 l of water with lid: 3 500 W:
3mn30s, 5 000 W: 2mn40s

Ventilated inductor housing

Type of use: heavy duty

Model with remote generator: distance
between generator and inductor up to 5 m.
Standard length of cable: 2 meters. Price of
the additional meter of cable: 20€, ref: CABLI1

Washable filter built in the remote generator

INTEGRATED GENERATOR

REMOTE GENERATOR

POWER	3 500 W	5 000 W	3 500 W	5 000 W
Power supply	230 V 40-60 Hz 1 phase 16 A + E + N	230 V 40-60 Hz 1 phase 20 A + E + N	230 V 40-60 Hz 1 phase 16 A + E + N	230 V 40-60 Hz 1 phase 20 A + E + N
Provided cable	3G2,5 mm ² without plug	3G2,5 mm ² without plug	3G2,5 mm ² without plug	3G2,5 mm ² without plug
REF Control panel	W3500ER	W5000ER	EWD3501B	EWD5001B
REF Knob	W3500ER POT	W5000ER POT	EWD3501M	EWD5001M