

# 2 HOB INDUCTION

## 900 RANGE

**SINGLE PHASE**

### INTEGRATED GENERATORS



Top cut: 376 x 696 mm  
Overall height: 190 mm

### USER COMMANDS



2 hob control panel

**NEW: inox frame + electronic card protection cover**



Control knob + LED indicator (1 per hob)

**NEW: removable housings for easy maintenance, no need to remove the ceramic glass**

- **Ceramic glass dimensions:** 370 x 690 mm, thickness 6 mm
- **Commands:**
  - Touch sensitive control panel, 16 power levels from 140 W to 3 500 W or from 200 W to 5 000 W
  - Or control knob with LED indicator
- **Utensil diameter:** 140 to 400 mm. Example of use: 1 pot of 400 mm + 1 frying pan of 280 mm, or 2 sauté pans of 340 mm, or a large fish pan of 600 x 180 mm
- **Inductor diameter:** 3 500 W: 210 mm, 5 000 W: 225 mm
- **Boiling time of 2 liters of water with lid:** 3 500 W: 3 mn 30s, 5 000 W: 2 mn 40s

### INTEGRATED GENERATORS

POWER	2 x 3 500 W	5 000 W + 3 500 W	2 x 5 000 W
Power supply	230 V 40-60 Hz Generator 1: 1 phase 16 A + E + N Generator 2: 1 phase 16 A + T + N	230 V 40-60 Hz Generator 1: 1 phase 20 A + E + N Generator 2: 1 phase 16 A + E + N	230 V 40-60 Hz Generator 1: 1 phase 20 A + E + N Generator 2: 1 phase 20 A + E + N
Provided cable	2x3G2,5mm <sup>2</sup> without plug	2x3G2,5mm <sup>2</sup> without plug	2x3G2,5mm <sup>2</sup> without plug
REF CONTROL PANEL	MF7000ER	MF8500ER	MF10000ER
REF CONTROL KNOB	MF7000ER POT	MF8500ER POT	MF10000ER POT