BUILT-IN

2 HOB INDUCTION

700 RANGE

SINGLE PHASE

INTEGRATED GENERATORS

Top cut: 376 x 586 mm
Overall height: 190 mm

NEW: removable housing for easy maintenance, no need to remove the ceramic glass

USER COMMANDS

2 hob control panel

NEW: inox frame + electronic card protection cover

Control knob
+ LED indicator
(1 per hob)

- **Ceramic glass dimensions**: 370 x 580 mm, thickness 6 mm
- **Commands:**
  - Touch sensitive control panel, 16 power levels from 120 W to 3 000 W or from 140W to 3 500 W
  - Or control knob with LED indicator

- **Utensil diameter:** 140 to 400 mm. Example of use: 1 pan of 350 mm + 1 frying pan of 180 mm, or 2 sauté pans of 280 mm
- **Inductor diameter:** 3 000 W: 195 mm, 3 500 W: 210 mm

- **Boiling time of 2 liters of water with lid:** 3 000 W: 4 mn 40s, 3500 W: 3 mn 30s
- **Type of use**: intensive

INTEGRATED GENERATOR

POWER	2 x 3 000 W	2 x 3 5000 W
Power supply	230 V 40-60 Hz Generator 1: 1 phase 13 A + E + N Generator 2: 1 phase 13 A + E + N	230 V 40-60 Hz Generator 1: 1 phase 16 A + E + N Generator 2: 1 phase 16 A + E + N
Provided cable	2x3G2,5mm² without plug	2x3G2,5mm² without plug
REF CONTROL PANEL	MF6000ER	MF7000ER
REF CONTROL KNOB	MF6000ER POT	MF7000ER POT

SEIPAM induction

technical specifications available on www.seipam.com

ORIGINE FRANCE GARANTIE AFNOR Cert. 651134 Fabrication Française