BUILT-IN

INDUCTION WOK

3 500 W - 5 000 W

SINGLE PHASE

INTEGRATED GENERATOR

Top cut: 376 x 376 mm
Overall height: 210 mm

USER COMMANDS

1 hob control panel

Control knob
+ LED indicator

NEW: **inox frame + electronic card protection cover**

NEW: **removable housings for easy maintenance, no need to remove the ceramic glass. Possible integration without the stainless steel frame.**

- **Ceramic glass dimensions**: Ø 300 mm, depth 70 mm, thickness 6 mm
- **Commands:**
  - Touch sensitive control panel, 20 power levels from 140 W to 3 500 W or from 200 W to 5 000 W
  - Or control knob with LED indicator
- **Inductor diameter:** 3 500 W: 210 mm, 5 000 W: 225 mm
- **Boiling time of 2 liters of water with lid**: 3 500 W: 3 mn 30s, 5 000 W: 2 mn 40s
- **Type of use**: intensive

INTEGRATED GENERATOR

POWER	3 500 W	5 000 W
Power supply Provided cable	230 V 40-60 Hz 1 phase 16 A + E + N 3G2,5mm² without plug	230 V 40-60 Hz 1 phase 20 A + E + N 3G2,5mm² without plug
REF CONTROL PANEL	WF3500ER	WF5000ER
REF CONTROL KNOB	WF3500ER POT	WF5000ER POT

SEIPAM induction

technical specifications available on www.seipam.com

ORIGINE FRANCE GARANTIE® AFNOR Cert. 651134 Fabrication Française